



MATERIAL SAFETY DATA SHEET

Manufacturer's name: WOODWRITE, LTD.
Address: 2121 Abell Lane
Sparks, MD 21152
Telephone number: 410-771-4444
Emergency telephone: 1-888-966-3974

Prepared by: Edward W. Underriner
Date prepared: March 4, 1997
Date revised: May 14, 1997

HMIS Rating:
Health: 3
Flammability: 3
Reactivity: 1
Personal protection: 1

Hazard Rating:
none ----- extreme
0 -----> 4

I - IDENTITY

Common name: Turner's Magic Super Gloss Polish (CN-17); Super Gloss
Proper shipping name: Paint
Hazard ID number: UN1263
Consumer commodity: Lacquer
C.A.S. number: None

Hazard class: 3
Packaging group: II
ORM-D: None (8 oz size)

II - INGREDIENT INFORMATION

Principal hazardous component(s):

	CAS No.	%	Threshold limit	VP (mm Hg)
Aliphatic Hydrocarbon	8052-41-3	13	TLV/PEL: N.E.*	12 (@ 100°F)
* NIOSH recommends a limit of 350mg/m ³ , 8 hour TWA, 1800 mg/m ³ as determined by a 15 minute sample.				
VM&P Naphtha - EC	64742-89-8	14	TLV/PEL: 300ppm	26 (@ 100°F)
Toluene	108-88-3	16	TLV/PEL: 100/50ppm	
Acetone	67-64-1	9	TLV/PEL: 750 ppm	
Methyl Alcohol	67-56-1	< 5	TLV/PEL: 200 ppm	
Xylene	1330-20-7	< 5	TLV/PEL: 100ppm	21 (@ 100°F)
Ethyl Benzene	100-41-4	< 1	TLV/PEL: 100ppm	7.1 (@ 68°F)
Isopropanol Anhydrous	67-63-0	< 5	TLV/PEL: 400ppm	33 (@ 68°F)
Isobutyl Isobutyrate	97-85-8	< 1	TLV/PEL: N.E.**	20.8 (@ 129°F)
**Eastman Chemical recommends exposure limit of 100ppm, 8 hr TWA.				
Butyl Cellosolve Acetate	112-07-2	< 5	TLV/PEL: N.E.	0.3 (@ 68°F)
Isobutyl Alcohol	78-83-1	< 1	TLV/PEL: 50ppm	8.8 (@ 68°F)

N.E. -- Not Established

III - PHYSICAL AND CHEMICAL CHARACTERISTICS

Boiling range: 180 - 250°F
Density: 7.25 lbs/gal
Percent volatiles: By Volume 64.2%
Solubility in Water: Insoluble
pH: Not applicable
Decomposition temperature: No information found
Viscosity: Thin liquid to heavy viscous material

Specific gravity: 0.87
Liquid density: Lighter than water
By weight: 57.8%
Appearance and odor: Amber liquid w/ solvent odor
Auto-ignition temperature: No information found

Vapor density: Heavier than air
Evaporation rate: 0.5 x n-Butyl Acetate
Corrosion rate: No information found

Turner's Magic Super Gloss Polish (CN-17)

IV - FIRE AND EXPLOSION HAZARD DATA

Flammability class: 1B **Flash point:** 35°F TCC **LEL:** 0.88% **UEL:** 12.70%
Extinguishing media: Foam, alcohol foam, CO₂, Dry Chemical, Water Fog
Special fire fighting procedures: Full fire fighting equipment with self-contained breathing apparatus and full protective clothing should be worn by fire fighters. Water may be used to cool closed containers to prevent pressure buildup, auto ignition or explosion.
Unusual fire and explosion hazards: Keep containers tightly closed. Isolate from heat, sparks, electrical equipment and open flame. Closed containers may explode when exposed to extreme heat. Application to hot surfaces requires special precautions. During emergency conditions, overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent.

V - HEALTH HAZARD DATA

Permissible exposure level: Sec II - Hazardous Ingredients, above.

Effects of overexposure:

Inhalation: Irritation of the respiratory tract and acute nervous system depression characterized by the following progressive steps: headache, dizziness, staggering gait, confusion, unconsciousness or coma.

Skin contact: Contact with the skin can cause irritation. Symptoms include swelling, redness and rash.

Eye contact: Liquid, aerosols or vapors are irritating and may cause tearing, redness and swelling, accompanied by a stinging sensation.

Skin absorption: Prolonged or repeated contact can cause moderate irritation, drying and defatting of the skin which can cause the skin to crack.

Ingestion:

Acute: Can result in irritation and possible corrosive action in the mouth, stomach tissue and digestive tract. Vomiting may cause aspiration of the solvent, resulting in chemical pneumonia.

Health hazards (acute and chronic):

Acute: Vapors are irritating to eyes, nose and throat. Inhalation may cause headaches, difficult breathing and loss of consciousness.

Chronic: Prolonged contact will cause drying and cracking of the skin, due to defatting action. Skin sensitization, asthma or other allergic response may develop.

Primary routes of entry:

Topical (Skin Contact):	Yes
Ingestion (Gastro-Intestinal):	No
Inhalation (Lungs):	Yes

Carcinogenicity: HTP? No IARC Monographs? No OSHA Regulated? No

Medical conditions generally aggravated by exposure: Asthma and any other respiratory disorders. Skin allergies, eczema and dermatitis.

First aid:

Inhalation: Move to an area free from risk of further exposure. Restore breathing. Asthmatic type symptoms may develop and may be immediate or delayed by several hours. Obtain medical attention.

Skin: Remove contaminated clothing. Wash affected areas thoroughly with soap and water. Wash contaminated clothing thoroughly before reuse.

Eyes: Flush with clean lukewarm water (low pressure) for at least 15 minutes, occasionally lifting eyelids. Obtain medical attention.

Ingestion: Do not induce vomiting. Do not give anything to an unconscious person. Obtain medical attention.

VI - REACTIVITY DATA

Stability: Unstable Stable

Hazardous polymerization: May occur Will not occur

Incompatibility: Strong oxidizing agents; strong acids.

Conditions to avoid: High temperatures; sparks; open flames.

Hazardous decomposition products:

By high heat/temperature: Carbon monoxide, carbon dioxide, oxides of nitrogen.

VII - SPILL OR LEAK PROCEDURES

Steps to be taken in case material is released or spilled: Evacuate all non-essential personnel. Remove all sources of ignition (flame, spark sources, hot surfaces). Ventilate area. Contain and remove with inert absorbent and non-sparking tools.

Waste disposal method: Waste must be disposed of in accordance with federal, state, and local environmental control regulations. Empty containers must be handled with care, due to product residue and flammable vapor. DO NOT incinerate closed containers. Also see Sections IV, V VI for other precautions.

EPA hazardous waste number/code: D001, F003, F005

Hazardous waste characteristics:

Ignitability:	Yes
Corrosivity:	No
Reactivity:	Yes

VIII - SPECIAL PROTECTION INFORMATION

Respiratory protection: A respirator that is recommended or approved for use in an organic vapor environment (air purifying or fresh air supplied) is necessary. Observe OSHA regulations for respirator use. Ventilation should be provided to keep exposure levels below OSHA permissible levels.

Ventilation: Exhaust ventilation sufficient to keep the airborne concentrations of solvent vapors or mists below their respective TLV's must be utilized. Remove all ignition sources (heat, sparks, flame and hot surfaces.)

Protective gloves: Protective gloves are recommended (cotton, neoprene, rubber, polyethylene) to prevent skin contact.

Eye protection: The use of safety eyewear is recommended, including splash guards or side shields, chemical goggles or face shields.

Other protective equipment: The use of long sleeves and long leg clothing is recommended. Remove and wash contaminated clothing before reuse.

IX - SPECIAL PRECAUTIONS

Precautions to be taken in handling and storage: Store in buildings designed to comply with OSHA 1910.106. Avoid storing near high temperatures, fire, open flames and spark sources. Store in tightly closed containers. Store in well ventilated areas.

Other precautions: Keep containers tight and upright to prevent leakage. Prevent prolonged breathing of vapors or spray mists. Prolonged overexposure may cause an allergic reaction. Avoid contact with skin and eyes. Do not take internally. Do not handle until the manufacturers safety precautions have been read and understood. Wash hands before eating, smoking or using washroom. Smoke in smoking areas ONLY.

*** TRANSPORTATION INFORMATION ***

Applicable regulations:	49CFR (yes);	IMCO (no);	IATA (no);
	Military Air (AFR 71-4) (no)		
Proper shipping name:	Paint	Hazard ID number:	UN1263
Reportable quantity:	Not applicable		
Hazard class:	Flammable liquid 3		

This material, when packaged in containers of 1 liter or less, qualifies as paint in limited quantities of Class 3.

Required labels:	Flammable liquid	3; This Side Up
US Postal Service regulations:	Not allowed to send via US Postal Service.	

*** DISCLAIMER ***

Information contained herein is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use of the materials and for the safety and health of their employees.

Actual VOC determined per EPA Reference Method 24.

X - REGULATORY INFORMATION

SARA 313:

This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right To Know Act of 1986 and of 40 CFR 372:

CAS number	Chemical name	Weight percentage
108-88-3	Toluene	16.00
67-56-1	Methanol	4.13
1330-20-7	Xylene	2.18
100-41-4	Ethyl benzene	0.44
67-63-0	Isopropanol anhydrous	2.31
71-36-3	n-Butyl alcohol	3.19
111-76-2	2-Butoxyethanol	5.90

STATE AND LOCAL REGULATIONS:**PROP 65 Carcinogenic:**

Warning: This product contains a chemical known to the state of California to cause cancer.

BENZENE

PROP 65 Teratogenic:

Warning: This product contains a chemical known to the state of California to cause birth defects or other reproductive harm.

TOLUENE

New Jersey RTK Label Information:

TOLUENE	108-88-3
ACETONE	67-64-1
NAPHTHA, SOLVENT	64742-89-8
METHYL ALCOHOL	67-56-1
ISOBUTYL ISOBUTYRATE	97-85-8

Pennsylvania RTK Label Information:

BENZENE, METHYL	108-88-3
2-PROPANONE	67-64-1
METHANOL	67-56-1

The information on this data sheet represents our current data and best opinion as to the proper use and handling of this product under normal conditions. Any use of the product which is not in conformance with this data sheet or which involves using the product in combination with any other product or any other process is the responsibility of the user.