#PKGCALL4

PSI Woodworking Products

Bite Style Cow Elk Predator Call Kit

Kit Features:

- Rigid ABS Plastic construction
- Designed by Game Call Professionals
- · Factory tuned sound board
- Lanyard optional

Required Accessories:

- Blank required: 1-1/2" x 1-1/2" x 3-1/2" to 4" L
- 7mm Pen Mandrel
- Wooden Jam Bushing set: #PKGCALL2BU
- Drill Bit: #PK-2132 (21/32") Dia.

Preparing the Blank:

- Cut a blank to the required length.
- · Mark the center of the square ends.
- Drill a 21/32" hole, centered through the length of the blank.



DIAGRAM B / TURNING THE BLANK SPACER SPACER BUSHINGS BUSHINGS LIVE **Reed Housing** CENTER Reed (2 pieces) MANDREL SAVER KNURLED NUT HEAD STOCK JAM BUSHING LANYARD GROOVE JAM BUSHING

Turning the Blank

- Mount spacer bushing and a jam bushing, wide end in first. Insert the blank and the remaining jam bushing narrow end in. Follow with spacer bushings. (see Diagram B)
- Use either a mandrel saver or a knurled nut to lock into place.
- Turn the blank down to the profile of your choice.
- Cut a groove to attach the lanyard cord.
- Sand and finish. Use penetrating oil for wood, or One-Step[™] plastic polish for acrylics.


Assembly

- Assemble the housing with the reed positioned as shown in Dia. "C".
- Snap the reed housing body together. Reed should not extend past the end of the reed housing.
- Push this assembly snug into the opening of the barrel, this should insert about mid way in.
- Attach the lanyard cord into the groove. Secure in place.

Tips & Techniques

- Draw Bull Elk and Coyotes in close with a true to life Cow Elk vocalization. To call Bull Elk, gently press the tip end of the call and give a short puff of air to create an "Eeeyahh" sound.
- For calling predators such as Coyote, Fox, Bobcat and Wolves, gently press the tip end and puff air to create a rabbit in distress sound.

DIAGRAM C / JAM BUSHINGS



© 2014 PSI Woodworking Philadelphia PA 19115 - v03/14

